

Ecolink Back-lit panel

- Uniform Brightness
- IK02 Impact Resistant
- Easy Installation
- IP20

ECOLINK panel is an affordable solution for office lighting which delivers reliable illumination to the needs of those customers who are looking for affordable and yet reliable LED products. Ecolink LED panels are an excellent replacement for their conventional TL equivalents.

Benefits:

- Guaranteed luminous flux and durability.
- Full window illumination – deliver comfortable light with excellent uniformity
- Energy Efficient.
- Simple and quick installation.



Product data

Optical system	
Power Rating (W)	42W (±10%)
Lumen output (typ.Avg)	3600lm (@6500k cct)
lumen output tolerance (+/-)	+10% , -10%
CRI	≥80
CCT	4000K / 6500K
SDCM	≤5
Uniformity	Backlit Technology, No visible shadow and yellow effect
UGR (office compliancy)	<22
Electronics	
Driver	External Driver (Non-Dimmable)
Input Voltage and Frequency	220-240V, 50/60Hz (±10%)
Power Factor (system)	>0.9
Power consumption (system)	42W (±10%)
System Efficacy	
Mechanical	85lm/w
IPxx	IP20
IKxx	IK02
Mounting	Recessed
Size (LxW)	597x597
	Tolerance : ±1
Thermal	
Operating temperature range	-10°C to +35°C
Reliability	
Lifetime	20k hrs (L70B50)

Product List

12 NC	Product Description
911401714923	Ecolink PL007B 42w/865 CLI 2x2
911401714913	Ecolink PL007B 42w/840 CLI 2x2
Accessories (Optional)	
911401867082	Panel SC SW
911401866982	Panel Suspension SW
911401866882	Panel PCV clip SW