

Ecolink TLED Batten BT007 C

Double Ended
LED tubes

Strong Wide
Metal Body

IP20

Whether for a new building or the renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. This product is one bare batten for matching any double end powered TLED product with elegant design and more safety.



Product data

Optical system	
Length (m)	L600,L1200
Voltage	220-240V~ 50/60Hz
IP rating	IP20
Wiring	Single and Double ended. Refer wiring diagrams
Insulation	Class I
Working temp	-20 ~ 40°C. (For Housing)
Connection	Inside wiring ; Middle entry;
Installation	Surface mounted, suspension
Housing material	SPCC
Housing coating	Powder painting, RAL9003
Housing thickness	0.3mm±0.02
Fuse	1000mA, with VDE
Accessory	Two screws: ST4x20mm ; two expansion bolts: 25xφ5.5mm *2
Packaging	PE Bag for each Batten, 40 Pcs in one Outercarton. One MI in each outercarton
Approbation	Compliant with IEC 60598

Product List

12 NC	Product Description
911401819382	Ecolink BT007C DE 2xTLED L1200 GM
911401819282	Ecolink BT007C DE 2xTLED L600 GM
911401819182	Ecolink BT007C DE 1xTLED L1200 GM
911401819082	Ecolink BT007C DE 1xTLED L600 GM